

Packing Instruction 965

Passenger and cargo aircraft for UN 3480

This entry applies to lithium ion or lithium polymer batteries.

Lithium batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

Waste lithium batteries and lithium batteries being shipped for recycling or disposal are prohibited from air transport unless approved by the appropriate national authority of the State of Origin and the State of the Operator.

SECTION II

Lithium ion cells and batteries offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium ion cells and batteries may be offered for transport if they meet the following:

- 1) for lithium ion cells, the Watt-hour rating (see the Glossary of Terms in Attachment 2) is not more than 20 Wh;
- 2) for lithium ion batteries, the Watt-hour rating is not more than 100 Wh;
 - the Watt-hour rating must be marked on the outside of the battery case except for those batteries manufactured before 1 January 2009;
- 3) each cell or battery is of the type proven to meet the requirements of each test in the UN *Manual of Tests and Criteria*, Part III, section 38.3.

Note.— Batteries are subject to these tests irrespective of whether the cells of which they are composed have been so tested.

General requirements

Batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

Contents	Package quantity (Section II)	
	Passenger	Cargo
Lithium ion cells and batteries	10 kg G	10 kg G

ADDITIONAL PACKING REQUIREMENTS

- Cells and batteries must be packed in inner packagings that completely enclose the cell or battery then placed in a strong outer packaging.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- Each package must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-31).
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium ion cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary;
 - a telephone number for additional information; and
 - the words “lithium ion batteries”, “not restricted” and “PI965” must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

OUTER PACKAGINGS

<i>Boxes</i>	<i>Drums</i>	<i>Jerricans</i>
Strong outer packagings		

Packing Instruction 966

Passenger and cargo aircraft for UN 3481 (packed with equipment) only

This entry applies to lithium ion or lithium polymer batteries packed with equipment.

Lithium batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

SECTION II

Lithium ion cells and batteries packed with equipment offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium ion cells and batteries may be offered for transport if they meet the following:

- 1) for lithium ion cells, the Watt-hour rating (see the Glossary of Terms in Attachment 2) is not more than 20 Wh;
- 2) for lithium ion batteries, the Watt-hour rating is not more than 100 Wh;
 - the Watt-hour rating must be marked on the outside of the battery case except for those batteries manufactured before 1 January 2009;
- 3) each cell or battery is of the type proven to meet the requirements of each test in the UN *Manual of Tests and Criteria*, Part III, section 38.3.

Note.— Batteries are subject to these tests irrespective of whether the cells of which they are composed have been so tested.

General requirements

Batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

ADDITIONAL PACKING REQUIREMENTS

- Cells and batteries must be packed in inner packagings that completely enclose the cell or battery.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- The maximum number of batteries in each package must be the minimum number required to power the equipment, plus two spares.

- Lithium ion cells or batteries must:
 - be placed in inner packagings that completely enclose the cell or battery then placed in a strong outer packaging; or
 - be placed in inner packagings that completely enclose the cell or battery, then placed with the equipment in a strong outer packaging.
- Each package of cells or batteries, or the completed package, must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-31).
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium ion cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary;
 - a telephone number for additional information; and
 - the words “lithium ion batteries”, “not restricted” and “PI966” must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

OUTER PACKAGINGS

Boxes

Drums

Jerricans

Strong outer packagings

Packing Instruction 967

Passenger and cargo aircraft for UN 3481 (contained in equipment) only

This entry applies to lithium ion or lithium polymer batteries contained in equipment.

Lithium batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

SECTION II

Lithium ion cells and batteries contained in equipment offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium ion cells and batteries may be offered for transport if they meet the following:

- 1) for lithium ion cells ,the Watt-hour rating (see the Glossary of Terms in Attachment 2) is not more than 20 Wh;
- 2) for lithium ion batteries, the Watt-hour rating is not more than 100 Wh;
 - the Watt-hour rating must be marked on the outside of the battery case except for those batteries manufactured before 1 January 2009;
- 3) each cell or battery is of the type proven to meet the requirements of each test in the UN *Manual of Tests and Criteria*, Part III, section 38.3.

Note.— Batteries are subject to these tests irrespective of whether the cells of which they are composed have been so tested.

Devices such as radio frequency identification (RFID) tags, watches and temperature loggers, which are not capable of generating a dangerous evolution of heat, may be transported when intentionally active. When active, these devices must meet defined standards for electromagnetic radiation to ensure that the operation of the device does not interfere with aircraft systems.

General requirements

Equipment must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

ADDITIONAL PACKING REQUIREMENTS

- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- Cells and batteries must be protected so as to prevent short circuits.

- The equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained.
- Each package containing more than four cells or more than two batteries installed in equipment must be labeled with a lithium battery handling label (Figure 5-31) (except button cell batteries installed in equipment (including circuit boards)).
- Each consignment with packages bearing the lithium battery handling label must be accompanied with a document with an indication that:
 - the package contains lithium ion cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary;
 - a telephone number for additional information; and
 - the words "lithium ion batteries", "not restricted" and "PI967" must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

OUTER PACKAGINGS

Boxes

Drums

Jerricans

Strong outer packagings

Packing Instruction 968

Passenger and cargo aircraft for UN 3090

This entry applies to lithium metal or lithium alloy batteries in Class 9 (Section I) and lithium metal or lithium alloy batteries subject to specific requirements of these Instructions (Section II).

Lithium batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

Waste lithium batteries and lithium batteries being shipped for recycling or disposal are prohibited from air transport unless approved by the appropriate national authority of the State of Origin and the State of the Operator.

SECTION II

Lithium metal or lithium alloy cells and batteries offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium metal or lithium alloy cells and batteries may be offered for transport if they meet the following:

- 1) for a lithium metal cell, the lithium content is not more than 1 g;
- 2) for a lithium metal or lithium alloy battery, the aggregate lithium content is not more than 2 g;
- 3) each cell or battery is of the type proven to meet the requirements of each test in the UN *Manual of Tests and Criteria*, Part III, section 38.3.

Note.— Batteries are subject to these tests irrespective of whether the cells of which they are composed have been so tested.

General requirements

Batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

Contents	Package quantity (Section II)	
	Passenger	Cargo
Lithium metal cells and batteries	2.5 kg G	2.5 kg G

ADDITIONAL PACKING REQUIREMENTS

— Cells and batteries must be packed in inner packagings that completely enclose the cell or battery then placed in a strong outer packaging.

- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- Each package must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-31).
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium metal cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary;
 - a telephone number for additional information; and
 - the words “lithium metal batteries”, “not restricted” and “PI968” must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

OUTER PACKAGINGS

Boxes

Drums

Jerricans

Strong outer packagings

Packing Instruction 969

Passenger and cargo aircraft for UN 3091 (packed with equipment) only

This entry applies to lithium metal or lithium alloy batteries packed with equipment.

Lithium batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

SECTION II

Lithium metal cells and batteries packed with equipment offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium metal cells and batteries may be offered for transport if they meet the following:

- 1) for a lithium metal cell, the lithium content is not more than 1 g;
- 2) for a lithium metal or lithium alloy battery, the aggregate lithium content is not more than 2 g;
- 3) each cell or battery is of the type proven to meet the requirements of each test in the UN *Manual of Tests and Criteria*, Part III, section 38.3.

Note.— Batteries are subject to these tests irrespective of whether the cells of which they are composed have been so tested.

General requirements

Batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

ADDITIONAL PACKING REQUIREMENTS

- Cells and batteries must be packed in inner packagings that completely enclose the cell or battery.
- Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
- The maximum number of batteries in each package must be the minimum number required to power the equipment, plus two spares.
- Lithium metal cells or batteries must:
 - be placed in inner packagings that completely enclose the cell or battery, then placed in a strong outer packaging; or
 - be placed in inner packagings that completely enclose the cell or battery, then placed with the equipment in a strong outer packaging.

- Each package of cells or batteries, or the completed package, must be capable of withstanding a 1.2 m drop test in any orientation without:
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
- Each package must be labelled with a lithium battery handling label (Figure 5-31).
- Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium metal cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary;
 - a telephone number for additional information; and
 - the words “lithium metal batteries”, “not restricted” and “PI969” must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

OUTER PACKAGINGS

Boxes

Drums

Jerricans

Strong outer packagings

Packing Instruction 970

Passenger and cargo aircraft for UN 3091 (contained in equipment) only

This entry applies to lithium metal or lithium alloy batteries contained in equipment.

Lithium batteries, identified by the manufacturer as being defective for safety reasons, or that have been damaged, that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport (e.g. those being returned to the manufacturer for safety reasons).

SECTION II

Lithium metal cells and batteries contained in equipment offered for transport are not subject to other additional requirements of these Instructions if they meet the requirements of this section.

Lithium metal cells and batteries may be offered for transport if they meet the following:

- 1) for a lithium metal cell, the lithium content is not more than 1 g;
- 2) for a lithium metal or lithium alloy battery, the aggregate lithium content is not more than 2 g.
- 3) each cell or battery is of the type proven to meet the requirements of each test in the UN *Manual of Tests and Criteria*, Part III, section 38.3.

Note.— Batteries are subject to these tests irrespective of whether the cells of which they are composed have been so tested.

Devices such as radio frequency identification (RFID) tags, watches and temperature loggers, which are not capable of generating a dangerous evolution of heat, may be transported when intentionally active. When active, these devices must meet defined standards for electromagnetic radiation to ensure that the operation of the device does not interfere with aircraft systems.

General requirements

Equipment containing batteries must be packed in strong outer packagings that conform to Part 4;1.1.1, 1.1.3.1 and 1.1.10 (except 1.1.10.1).

ADDITIONAL PACKING REQUIREMENTS

- The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation.
- Cells and batteries must be protected so as to prevent short circuits.
- The equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the battery is afforded equivalent protection by the equipment in which it is contained.

- Each package containing more than four cells or more than two batteries installed in equipment must be labeled with a lithium battery handling label (Figure 5-31) (except button cell batteries installed in equipment (including circuit boards)).
- Each consignment with packages bearing the lithium battery handling label must be accompanied with a document with an indication that:
 - the package contains lithium metal cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary;
 - a telephone number for additional information; and
 - the words “lithium metal batteries”, “not restricted” and “PI970” must be placed on the air waybill, when an air waybill is used.
- Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

OUTER PACKAGINGS

Boxes

Drums

Jerricans

Strong outer packagings